



EL-IPR272-MV

2M Bullet IP Camera

72pcs LED,

電動變焦鏡頭

Key Feature

- 低照度 (0.006 Lux)於低光源有最佳表現
- 數位寬動態
- 支援 3DNR 降噪功能
- 4X 自動變焦鏡頭可由 DVR 遠端控制.
- H.264 壓縮(High / Main profile) 及 MJPEG 影像壓縮格式
- Full HD 1080P@30 fps + D1@30 fps
- 80M 紅外線
- 雙向語音
- 可設定字幕及遮罩功能
- 網路斷訊自動檢查
- IP66 防水
- 支援 海康及 Onvif 協議

| | |
|------------------------|--|
| Model | EL-IPR272-MV |
| System | |
| 處理器 | Dual-core embedded processor |
| 操作系統 | Embedded LINUX |
| Image Sensor | |
| 影像晶片 | 2M, 1/3" Progressive Scan CMOS, Sony IMX322, |
| 解析度 | 1920x1080 |
| 鏡頭 | |
| Lens Type | 電動變焦 |
| Focal Length | f=2.8~12mm |
| Aperture | F2.0 |
| Zoom | 4X |
| 攝影機 | |
| Shutter Time | 1/5 to 1/32,000 Sec |
| WDR | Digital WDR, (on/off) |
| Day & Night | Removable IR -cut filter for day& night function |
| Minimum Illumination | 0.1 Lux@ F2.0(Color); 0.006Lux(B/W); 0 Lux @ IR LED ON |
| IR Illumination | Build-in IR illuminators, effective up to 80 meters (depending on environment) |
| On-board Storage | optional |
| 影像及聲音 | |
| Compression | H.264 & MJPEG |
| Maximum Frame Rate | 30 fps@1920x1080 |
| Maximum Streams | 2 |
| S/N Ratio | More than 53 dB |
| Video Streaming | Adjustable resolution, quality and bitrate; Resolution: 1920*1080; 1280*960; 1280*720; 720*480 Bitrate: main stream 512K ~ 6M Sub-stream: 128K ~1M |
| Image Setting | <ul style="list-style-type: none"> Adjustable image size, quality and bit rate Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks Scheduled profile settings, 3D Noise Reduction |
| Audio | G.711, 1 In 1 Out |
| 網路 | |
| Users | Live viewing for up to 5 users |
| Protocols | TCP/IP, HTTP, ICMP, UDP, SMTP, RTP, RTSP, SNMP, ARP , DDNS , DNS , PPPOE , P2P,802.1X , SCTP , NTP |
| Interface | 10 Base-T/ 100Base TX Ethernet (RJ-45) |
| Onvif | Supported, specifications available at www.onvif.org |
| 動態功能設定 | |
| Motion Detection | Quad-windows video motion detection |
| Motion Detection Out | Event notification using digital output, HTTP, SMTP |
| Video Privacy Masking | Quad masking zones |
| 其他 | |
| Power Supply | DC 12V; IEEE 802.3AF POE |
| Power Consumption | Max. 6.5W (DC 12V); Max 7.5W (POE) |
| Working Environment | -20°C~+50°C / 10%~90%RH / 86~106kpa |
| Weather Proof Standard | IP 66 |
| Weight | Less than 0.9Kg |